



TEL- AVIV / BEN-GURION (LLBG)
ILS RWY 26



CHANGES: Directions: Missed approach procedure and description. Holding @ BGN VOB deleted. MSA sectors. MAG VAB. coding table. chart designator.

TRANSITION ALT 18 000



- 1 RNAV1 Required for initial segment.
If unable RNAV1 expect radar vectors to ILS.
- 2 GP INOP + CIRCLING - not Authorized.

LLBG RWY26 ILS CAT I Initial Approach

Navigation specification	Path Descriptor (Recommended)	Waypoint Identifier	Latitude Longitude	Flyover	Course/Track M° (T°)	Distance (NM)	Turn Direction	Altitude (ft)	Speed (Kts)	Remarks
RNAV1	IF	RABIN	32° 07' 32.2" N 035° 07' 20.9" E	FB				+3 800	-210	IAF
RNAV1	TF	GINTU	32° 04' 48.4" N 035° 09' 58.2" E	FB	136 (140.7)	3.5		+3 800	-185	
RNAV1	TF	LASRI	32° 03' 12.4" N 035° 07' 41.7" E	FB	225 (230.4)	2.5		+3 400	-185	IF

RWY26 ILS Intermediate and Final Approach

Fix	Fix Coordinates	True Azimuth (M) (reference)	DME distance
IF	32° 03' 12.4" N 035° 07' 41.7" E	079.8 true (075) (LOC26)	12.2 DME BA * 13.1 DME BGN
FAP	32° 02' 47.9" N 035° 04' 59.1" E	079.8 true (075) (LOC26)	9.9 DME BA * 10.8 DME BGN
RWY26	32° 01' 03.8" N 034° 53' 33.9" E		0.9 DME BGN
DER26	32° 00' 44.0" N 034° 51' 24.0" E		

* 0 at THR

ILS RWY26 Missed Approach

Navigation specification	Path Descriptor (Recommended)	Waypoint Identifier	Latitude Longitude	Flyover	Course/Track M° (T°)	Distance (NM)	Turn Direction	Altitude (ft)	Speed (Kts)	Remarks
RNP APCH	CA			-	255 (260.0)			+600	-220	
RNP APCH	CF	BG070	32° 01' 16" N 034° 44' 20" E	-	270 (275.0)		R	@ 3000	-220	
RNP APCH	FM			-	270 (275.0)			@ 3000		